

Specification



- Permanent anti-freezing system
- Damage-resistant housing
- Speech synthesizer for customer service
- Records the acceptance of payments
- Cash-banknote/card payment/PayPass modes
- Made in compliance with TÜV standards
- Fireproof housing
- Gorilla Glass – scratch-resistant glass
- GPRS system – daily e-mails sent to the owner with a cash/time report
- LED lighting with visibility function for the driver passing at a distance of 25m
- Adjustable colour scheme with logotype according to the specification

Full technical parameters

Maximum working steam pressure

max. 8 bar (116 PSI)

Steam operating temperature

120-140 °C or 234-273 °F

Boiler temperature

max. 190 °C thermostat/auto stop

Number of boilers

1

Preferred connections

electricity / water – optional sewage – optional
(from concrete foundations)

Warm-up time

immediate readiness

Tank capacity

water or fixed connection / detergent 75 l / 75 l

Operation volume

60-74 dB

Voltage and frequency

400 V / 50-60 Hz or 240 V / 50-60 Hz

Dimension

250 cm (98 in) W x 140 cm (55 in) L x 220 cm (87 in) H

Net weight

850 kg

Standard accessories

insulated steam extraction hose (8 m / 30 ft.): 1 pcs
anti-burn washing gun with small nozzle for upholstery washing: 1 pcs.
dry-wet Ghibli & Wirbel vacuum cleaner: 1 pcs.
keyboard and mouse set: 1 pcs.

GSM modem

1 pcs.

Coin acceptor (banknotes and/or payment card acceptor is not a part of the standard equipment):

1 pcs.

Housing material

aluminium

Boiler material

boiler steel

Anti-burglary system

YES

Hot detergents system

YES

STOP emergency button

YES

Continuous operating mode 24/7/365

YES

Anti-shock security system

YES

Cooling system and high temperature operation

YES

Warming-up and ant-freezing system

YES

Electrical power consumption reduction mode

YES

19" LCD touch screen – functions:

cash register application; work mode monitoring with auto-reporting of failures; cash register reports with e-mailing function every 24 hours; detergent washing mode, no-detergent washing mode for allergic users, just-vacuuming mode; remote diagnosis and maintenance; Time Viever; service panel; launching of detergent feeding from the machine.

Power consumption

6,5 kW